

Range AL with SOLENOID VALVE

The SUNTEC AL oil pump incorporates a blocking solenoid valve with in-line cut-off function. Bleeding in two-pipe operation is automatic. In one-pipe operation, the plug of a pressure gauge port must be loosened until the air is evacuated from the system..

Delivered without connector



Type	Flow l/h to 2800 tr/mn and 10 bars	M=Hub B=Flange Ø=Shaft	Features	Rotation	Outlet nozzle side	Pressure	Ref
AL 30 C 9537 4P 0500	40	M 32 x 8	-	←	←	8/15	301946
AL 35 A 9526 2P 0500	40	M 32 x 8	-	→	→	8/15	301949
AL 35 A 9570 2P 0500	40*	M 32 x 8	-	→	→	8/15	301958
AL 35 A 9596 2P 0100	40*	M 32 x 8	(7)	→	→	8/15	301936
AL 35 A 9596 2P 0500	40*	M 32 x 8	-	→	→	8/15	301869
AL 35 B 9520 2P 0200	40	M 32 x 8	(4)	→	←	2/12	301937
AL 35 B 9520 2P 0300	40	M 32 x 8	(8)	→	←	2/12	301945
AL 35 B 9520 2P 0500	40	M 32 x 8	-	→	←	2/12	301872
AL 35 B 9580 2P 0500	40*	M 32 x 8	-	→	←	8/15	301956
AL 35 C 9521 2P 0100	40	M 32 x 8	(7)	←	←	4/18	301938
AL 35 C 9521 2P 0500 or AL 35C 9519 6P 0500	40	M 32 x 8	-	←	←	4/18	301873
AL 35 C 9528 2P 0500	40	M 32 x 8	-	←	←	8/15	301957
AL 35 C 9540 2P 0500	40	M 32 x 8	(1)	←	←	8/15	301950
AL 35 C 9542 2P 25RA	40	M 32 x 8	(11)	←	←	8/15	301954
AL 35 C 9545 1P 0500R	40	M 32 x 8	(1)	←	←	8/15	301950
AL 35 C 9578 2P 0500R	40*	M 32 x 8	-	←	←	8/15	301987
AL 35 D 9529 2P 0200	40	M 32 x 8	(4)	←	→	8/15	301959
AL 35 D 9529 2P 0500	40	M 32 x 8	-	←	→	8/15	301939
AL 35 D 9595 2P 0500	40	M 32 x 8	(9)	←	→	8/15	301939
AL 55 B 9531 2P 0500	60	M 32 x 8	-	→	←	4/18	301875
AL 55 C 9598 2P 0500	60	M 32 x 8	(6)(9)	←	←	10/25	301986
AL 65 B 9532 2P 0500	82	M 32 x 8	-	→	←	4/18	301877
AL 65 B 9581 2P 0100	82	M 32 x 8	(7)	→	←	12/25	301944
AL 65 B 9581 2P 0500	82	M 32 x 8	-	→	←	12/25	301878
AL 65 C 9410 2P 0500	82*	B 54 x 8	-	←	←	4/18	301879
AL 65 C 9525 2P 0500	82	M 32 x 8	(5)	←	←	8/15	301980
AL 65 C 9588 2P 0500	82*	M 32 x 8	-	←	←	8/15	301981
AL 65 C 9589 2P 0500	82	M 32 x 8	-	←	←	8/15	301982
AL 75 B 9539 2P 0500	110	M 32 x 8	-	→	←	8/15	301880
AL 75 C 9411 2P 0500	110*	B 54 x 8	-	←	←	4/18	301881
AL 75 C 9534 2P 0500	110	M 32 x 8	(5)(6)	←	←	8/15	301983
AL 95 C 9412 2P 0500	132*	B 54 x 8	-	←	←	10/20	301984
AL 95 C 9414 2P 0500	132*	B 54 x 8	(10)	←	←	10/20	301882

(1) Inlet and Return. 1/8" - (2) long outlet nozzle - (3) Type one-pipe - (4) Coil 24VAC.

(5) Conical ripple Ø4 - (6) Kerosene - (7) Coil 110VAC - (8) Coil 24VDC - (9) Adjusting screw pressure on the nozzle side.

(10) Shaft with 2 flat surfaces - (11) Coil with cable power. * With outlet air jack.